

WEST**End of Result Set**

Generate Collection

Print

L2: Entry 3 of 3

File: DWPI

Apr 27, 1997

DERWENT-ACC-NO: 1997-501236
DERWENT-WEEK: 199746
COPYRIGHT 2003 DERWENT INFORMATION LTD

TITLE: Filter element for liquids and gases - comprises filter partition in the form of cylindrical helix with sinusoidal windings, lid and nozzle at opposite ends, and elastic element between frame and lid

INVENTOR: KRAPUKHIN, V B

PRIORITY-DATA: 1992RU-0014963 (December 29, 1992)

PATENT-FAMILY:

PUB-NO	PUB-DATE	LANGUAGE	PAGES	MAIN-IPC
RU 2077925 C1	April 27, 1997		004	B01D029/48

INT-CL (IPC): B01 D 29/48

ABSTRACTED-PUB-NO: RU 2077925C
BASIC-ABSTRACT:

The filter element comprises filter partition (1), frame (2), elastic element (3), lid (4), and nozzle (5) for input and output of liquid or gas. The filter partition (1) is made in the form of screw helix with sinusoidal windings. The loops of winding are made by a sinusoid folded along helix. The sinusoidal curve can be in the plane of windings (fig. 2), or in the plane parallel to the axis of filter element (fig. 3). The filter spacing in the first variant is determined by the length l between neighbouring crests of sinusoidal wave, and distance a between troughs. The frame can be placed on outer or on inner side of filter partition.

USE - In devices for filtration of liquids and gases, in particular of radioactive and corrosive liquids and gases in nuclear and thermo-electric power plants, in petroleum and chemical branches of industry, in transport vehicles for purification of fuel, oil and air, in production of paints, in building and food-processing branches of industry, and in households for purification of water.

ADVANTAGE - Increase productivity of filter element.